

## Manufacturer Declaration

Manufacturer: **Yokogawa Process Analyzers Europe B.V.**

Address: Euroweg 2  
3825 HD Amersfoort  
The Netherlands

Product description: **SC29C(D)-PTP29, Redox electrode**  
**SM29-PT9, Redox electrode**  
**SC29-PTG29, Redox electrode**

### Statement:

The electrode meets the requirements given by the standard IEC 60079-11:2011, "Explosive atmospheres – Part 11: Equipment protection by intrinsic safety "i". Within the standard it falls into the category "**simple apparatus**" (clause 5.7(a), passive component).

The electrode has no internal voltage and/or current-limiting and/or suppression devices and does not contain any means of increasing the available voltage or current.

The electrode itself has negligible internal inductance and capacitance. The connection cable, type WU20-PC or WU20-LT or WF10 in combination with BA10 connection box, has a maximum inductance of 1µH/meter and a maximum capacitance of 1.5nF/meter.

The maximum power dissipation of the Redox electrode is considered negligible because no dissipating components are inside.

Special conditions of use must be taken into consideration:

- The electrode may only be connected to an intrinsically safe certified Yokogawa analyzer model PH202S, FLXA21 and FLXA202, with a maximum connection cable length of 60 meters in between the electrode and analyzer.
- Electrostatic charges of the electrode enclosure parts shall be avoided, especially in the case that the process medium is non-conductive. Use a damp cloth for cleaning the electrode.
- When the electrode is located in the explosive atmosphere, the maximum process temperature depends on the temperature class. Values are defined in table 1.

**Table 1:** Upper limit of process temperature SC29 and SM29 models


Temperature Class	Max. Process temperature [°C]		
	SC29C(D)-PTP29	SM29-PT9	SC29-PTG29
T6	80	80	80
T5	95	95	95
T4	100 *	130	100 *
T3	100 *	130 *	100 *
T2	100 *	130 *	100 *
T1	100 *	130 *	100 *


\*: Max. Process temperature is limited by the operating temperature of the electrode.

If applicable, the product is checked against the latest official released revision of the standards mentioned above. Differences do not affect the product identified on this declaration.

Amersfoort – September 15, 2020

Yokogawa Process Analyzers Europe B.V.

  
T. Both  
Safety Engineer

  
S. Kiyono  
General Manager